

Subsurface Constructors

Ground Improvement

Community Supervision Center Liquefaction Mitigation



Subsurface Constructors

Vibrocompaction and aggregate piers to mitigate liquefaction near fault line

This project involved construction of the new Community Supervision Center in Kennett, Missouri, a town located less than an hour from the New Madrid Fault. Given the facility's seismic risks, liquefaction of existing loose and silty sands was a significant concern.

Subsurface Constructors provided a ground improvement design, consisting of vibrocompaction to densify existing sands and aggregate piers/vibro stone columns to support the structure. Soils at the site consisted of alluvial sandy clays and silts overlying relatively clean, loose to medium sand.

We constructed 970 aggregate piers/vibro stone columns to improve the soft upper soil to a post-treatment bearing pressure of 2,500 pounds per square foot. At each of these locations, we first used vibrocompaction in the underlying sands to mitigate for liquefaction. Our team employed post-treatment modulus testing and borings with SPT testing to verify the design parameters. Post-treatment SPT (N) blow counts in the sands were often three to four times the initial values, indicating a significant strength increase of this layer.

Project details:

Owner: Missouri Department of Corrections

Geotechnical Engineer: Holcomb Foundation Engineering

General Contractor: Brown Construction

Structural Engineer: Robert Stearnes & Associates

Services Provided: Ground Improvement, Aggregate Piers/Vibro Stone Columns, Value Engineering

Year: 2007

Location: Kennett, Missouri